



- Introduced to meet the needs of project builders seeking an ultra low cost yet performance downlight.



**New!**

### FEATURES

- Plastic downlight with internal aluminium heat sink
- High efficiency SMD chips
- Constant current driver
- Opal polycarbonate diffuser
- IC-F and IC-4 rating. May be installed under ceiling insulation
- Removable flex and plug
- 6mm terminals for hard wiring

### DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

### INCLUDES

- Fixed head LED downlight
- Build-in dimmable LED driver
- 1.2 m flex and plug

### APPLICATIONS

- Residential
- Hotels and shops
- Conference rooms
- Reception areas
- Bathrooms and wet areas

### WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION			IP RATING	DIMMABLE	DISTRIBUTION	DIMENSIONS(mm)
				 leading and trailing edge		

Part No.	Voltage	Watt.	PF	CCT.	Ra	Lumen	Beam Angle	Lifetime L70B50	Fitting Colour
172031A	220-240V	9W	0.9	3000K	≥80	750lm	100°	35000h	White
172032A	220-240V	9W	0.9	4000K	≥80	800lm	100°	35000h	White
172061A	220-240V	9W	0.9	5000K	≥80	800lm	100°	35000h	White

Part No.	Model No.	VEET Status	IPART Status
172031A	YKRS3F5A-D 9W	Approved VEET No.: 4914	Approved IPART No.: 24143D15-K6EGGJ
172032A	YKRS3F5A-D 9W	Approved VEET No.: 4914	Approved IPART No.: 24143D15-K6EGGJ
172061A	YKRS3F5A-D 9W	Approved VEET No.: 4914	Approved IPART No.: 24143D15-K6EGGJ

[1] Operating Frequency=50/60Hz

[2] Switch Times≥20000

[3] This fitting is IP54 only once installed

[4] For dimming compatibility please see page 85

